

# HSC900 -H5551 SIDE CURTAIN



## Side Curtains for trucks and trailers

Feature	Benefit
<ul style="list-style-type: none"> <li>- Tentering frame technology (for material flatness)</li> <li>- Excellent weldability</li> <li>- Less smoke during welding</li> </ul>	<p>Optimal processing = Significant lower fabrication costs</p>
<ul style="list-style-type: none"> <li>- Excellent soiling behavior</li> <li>- Colours matching RAL scale</li> <li>- One of the best silvers in the market</li> </ul>	<p>Heytex Surface Guarantee = Outstanding optics and long lifespan</p>
<p>DIN 9001 certification + Intensive control and testing of every batch</p>	<p>Perfect reliability = No need for strong substandard tarpaulin or costly return shipments</p>

Available: Ex-stock

Roll Width:  
300cm & 320cm select colours

Roll Length: 58m

Other width & roll lengths on request



## Available colours

1003 Yellow	300cm 320cm
2008 ORANGE	300cm
3002 Red	300cm 320cm
5002 Blue	300cm
5013 Cobalt Blue	300cm 320cm
5561 Royal Blue	300cm 320cm
3109 Burgundy	300cm

6005 Dark Green	300cm 320cm
7701 Grey	300cm
7035 Light Grey	300cm
7037 Dust Grey	300cm 320cm
9005 Black	300cm 320cm
9006 Silver	300cm
9016 White	300cm 320cm

\*Print White glossy also available

# TECHNICAL DATA

## HSC900 - H5551



**Base fabric (DIN ISO 2076)**

100% Polyester



**Total weight (DIN EN ISO 2286-2)**

ca. 900 g/m<sup>2</sup> | 27 oz/yd<sup>2</sup>




**Coating material**

PVC



**High gloss finish**



**Tensile strength**

DIN EN ISO 1421-1

≥ 4000/4000 N/5 cm  
≥ 457/457 lbs/inch



**Tear resistance**

DIN 53363

≥ 550/500 N  
≥ 124/112 lbs



**Welding adhesion**

IVK 3.13

≥ 100 N/5 cm  
≥ 11 lbs/inch



**Temperature resistance**

DIN EN 1876-1

-30 °C to +70 °C  
-22 °F to +158 °F



**Light fastness**

ISO 105 B02

7-8



**Flex resistance**

DIN 53359 A

At least 100,000 bends



**Flame retardancy**

ISO 3795

Max. 100 mm/min  
Max. 3.9 inch/min



**EU guideline for curtainsiders**

DIN EN 12641-2

Complies