

RIPTECH CANVAS FR 320

TECHNICAL DATA

PRODUCT DESCRIPTION

Name	Riptech Canvas Black FR 320
Description	Acrylic treated polyester plain weave fabric
Benefits	Waterproof / UV Resistant / Fungal Resistant
Code	PWCPETFRBLK320

SPECIFICATIONS

PROPERTY	FR 320	METHOD
Composition	Polyester/Acrylic	-
Construction	Plain Weave	-
Weight	400gsm +5%	-
Width	3200mm	-
Water Penetration	> 1000mm	ISO 811:1981
Tensile Strength	Warp > 1800N/5cm	BS 13934-1:1999
	Weft > 1400N/5cm	
Colour Fastness to Light*	> 6	ISO 105-BO4
Fungal Resistance	Pass	Acti-Chem M/L13
Flammability	Pass	BS 7837:1996

MANUFACTURER:



SHRINKAGE UNDER HEAT RESULTS

	INITIAL DIMENSION	190°C - 5 MIN		160°C - 5 MIN	
		WARP	WEFT	WARP	WEFT
400GSM	350mm	326mm	335mm	338mm	342mm
	% SHRINKAGE	0.00%	6.86%	4.29%	3.43%
500GSM	350mm	330mm	345mm	336mm	348mm
	% SHRINKAGE	0.00%	5.71%	1.43%	4.00%

2 year warranty: This applies to the entire range of RIPTECH® fabrics. The fabric is guaranteed for a period of two years for structural integrity of the fabric, given normal exposure to weather and cleaning of the fabric is completed in accordance with the correct cleaning instructions. This warranty does not cover damages caused by accidents, mechanical action, rubbing, chemical aggressive agents, abuse and / or negligence. Please note that (1) darker colours will fade quicker than lighter colours, based on results obtained on Master samples tested to the ISO 105-B04 standard, (2) Shrinkage Under Heat results are indicative and do not constitute a specification, (3) the information shared in this document is for general information only, and it is the responsibility of the customer to ensure that this product meets their specific requirements. The data in this document is for indication only and the product performance properties may vary. This document is not to be treated as a Certificate of Conformance. Manufacturer will not entertain any damages claimed against them as a result of data expressed in this document.