

## AMBIENTE 42 DESIGNER COLORS

<b>Thickness</b>	<b>Hide type</b>	<b>Average size</b>
0.9 – 1.1 mm	European Bovine	4.6-5 sqmt ( 48-55 sqft )

<i>Water and stain repellent already dyed into leather</i>
<b>HIGH TRAFFIC AREA FRIENDLY</b>
RESIDENTIAL – CONTRACT – HOSPITALITY – AVIATION - MARINE - FASHION

### TECHNICAL SPECIFICATIONS

Test	Test method	Mesurment unit	Resoult
Tear strenght-Single edge tear	UNI EN ISO 3377-1	N	➤ = 20
Colour fastness to rubbing dry 500 cycles	UNI EN ISO 11640:1998	Grey scale	➤ = 4
Colour fastness to rubbing wet 250 cycles	UNI EN ISO 11640:1998	Grey scale	➤ = 4
Colour fastness to rubbing sweat 80 cycles	UNI EN ISO 11640:1998 ISO 11641 pH8	Grey scale	➤ = 4
Flexing endurance dry 50.000 cycles	UNI EN ISO 5402		No damage
Finish adhesion dry	UNI EN ISO 11644	N/Cm	➤ = 2
Colour fastness to artificial light Exposition energy 16.000 kj/sqm	UNI EN ISO 105 B02 (MET5)	Blue scale	➤ = 5
Burning behaviour to cigarette and match flame	BS 5852:1979 BS EN 1021-1-2-:2006		Pass
	NFPA 260		Pass
	CAL TB 170		Pass
	IMO Res. MSC (36)63 – (1994HSC Code) 7 IMO Res. MSC 97(73) – (2000HSC Code) 7 IMO Res. MSC 307(88) – (2010FIP Code) Imo/msc/Circ 1120		Pass

**LEATHER  
MADE IN ITALY**

	FAR 25.853 (a) and FAR 25.853 (b) APPLICABLE ON REQUEST		
--	---	--	--

The test results are referred only to the sample tested

THE PRODUCT COMPLIES WITH THE **REACH** REGULATION

LEATHER  
MADE IN ITALY