

## SHANNTAC 30

### Product description

Shann TAC 30 is a very high quality heat-resistant contact adhesive for gluing EPDM, Rubber, TPO, HPL, wood and all types of synthetics (except PE and PP).

### Material

SBR polymer mix

### Properties

- Very powerful
- Heat resistant
- Extremely powerful
- Fast drying
- For universal use
- Ready to use

### Areas of application

For gluing all types of EPDM (American and European) and almost all types of roof covering, on all surfaces. Easy Contact X30 has various test certificates and has been approved under the new standards of the ATG and the EU directive on surface adhesives.

### Instructions

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive onto both surfaces being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 2-4 minutes and press or roller firmly. Wait at least twice as long to glue the surfaces together if the layers applied have overlapped. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

### Available forms

Spray can 750ml

Pressurised cylinder 17l

### Colour

Transparent

### Surface

All surfaces should be dry and free from grease and dust.

### Safety recommendations

See safety information sheet

### Technical data

Properties	Specification
Processing temperature	+5 to +40 degrees
Temperature resistance	-40 to +130°C

