



Revision Date: 3/16/2020
 Approved by: RR
 Version: TL-0

PRODUCT SPECIFICATION

PRODUCT ID # : 9234-30120-559

EPT Xtrm Ply PW White 9234 - 30 oz - AS/NZS 4020:2018, NSF 61

Base Fabric

Weight 2.6 oz/yd² (88 g/m²)
 Yarn Polyester

Coating

Polymer EIA/KEE
 Color White
 Sealing RF, Hot Air, Wedge
 Width 60.0 in 120 in

Physical Properties	Units	Test Method	Typical value	
Thickness	mils	ASTM D751	34.0 (± 5%)	
	mm		0.86	
Weight	oz/yd ²	ASTM D751	30	
	g/m ²		1017	
Tear Strength (Tongue Tear)	lbs	ASTM D751- B	35 (MD)	35 (TD)
	N		156 (MD)	156 (TD)
Breaking Strength (Grab Tensile)	lbs	ASTM D751-A	175 (MD)	175 (TD)
	N		778 (MD)	778 (TD)
Adhesion- Ply	lb/in	ASTM D751	10	
	N/25mm		44	
Low Temperature Bend Test (1/8" Mandrel, 4 hours)	°F	ASTM D2136	-25	
	°C		-32	
Dimensional Stability (Max)	%	ASTM D1204	3.0%	

This product conforms with NSF/ANSI 61 Drinking water system components - Protective Barrier Materials (≥ 300 gal.)

Product Specifications are minimum values, actual results may be higher

We believe this information is the best currently available on the subject. It is provided as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge, information and experience are gained. We make no guarantee of results and assume no obligation, warranty or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply

