

## ELEGANTE 29 DESIGNER COLORS

<b>Thickness</b>	<b>Hide type</b>	<b>Average size</b>
1.1 – 1.3 mm	European Bovine	4.6 – 5 sqmt (48-55 sqft)

<i>Water and stain repellent already dyed into leather</i>
<b>HIGH TRAFFIC AREA FRIENDLY</b>
RESIDENTIAL – CONTRACT – HOSPITALITY – AVIATION - MARINE - FASHION

### TECHNICAL SPECIFICATIONS

Test	Test method	Measurement unit	Result
Thickness	ISO 2589	mm	1.1 – 1.3
Colour fastness to rubbing – Cycles - Dry	UNI EN ISO 11640 ISO 105-A02	Grey scale	1500/ > = 4
Colour fastness to rubbing – Cycles - Wet	UNI EN ISO 11640 ISO 105-A02	Grey scale	400/ > = 4
Colour fastness to rubbing – Alkaline sweat solution	UNI EN ISO 11640 ISO 105-A02 / ISO 105-E04	Grey scale	80/ > = 4
Adhesive strenght of finish	ISO 11644	N/Cm	➤ = 4
Tensile strenght	ISO 3376	N	➤ = 130
Tear propagation force	ISO 3377-1	N	➤ = 20
Stitch Tear Resistance	ISO 23910	N	➤ = 50
Behavior at permanent folding – 50.000 cycles	UNI ISO 5402	Visual Evaluation	No damage
Color fastness to light – 72h	ISO 105 B06	Grey scale	➤ = 4
Aging	4h at 70° C	Visual Evaluation	Min 4
Flammability	FMVSS 302	Mm/min	< = 100
pH value	ISO 4045		➤ = 3.5
Difference Figure – only for pH > 4 or > 10	ISO 4045		< = 0.7
Burning behaviour to cigarette and match flame	BS 5852:1979 BS EN 1021-1-2-:2006		Pass
	NFPA 260		Pass
	CAL TB 170		Pass

**LEATHER  
MADE IN ITALY**

	FAR 25.853 (a) and FAR 25.853 (b) APPLICABLE ON REQUEST		
--	---	--	--

The test results are referred only to the sample tested

THE PRODUCT COMPLIES WITH THE **REACH** REGULATION

LEATHER  
MADE IN ITALY